



MULTIPURPOSE WATERTIGHT LUMINAIRE FOR DECKS, STORES, ENGINE ROOMS

<b>Design</b>	According to rules of maritime classification societies and relevant standards
<b>Housing</b>	Galvanized steel, powder coated white (RAL9016)
<b>Cover</b>	LED: Opal polycarbonate, Fluorescent: Satin polycarbonate, impact-proof, UV resistant
<b>Mounting</b>	2 mounting holes, Ø 9 mm
<b>Cable entry</b>	2 cable glands M20, LED: nickel plated brass Fluorescent: PA 6
<b>Protection class</b>	IP67
<b>Voltage</b>	220-240 V AC
<b>Frequency</b>	50-60 Hz

### LED SOLUTION

TL09	5105009800-004
Light source	LED module
Weight	1.5 kg
Wattage	Max. 4 W
CCT (color)	4,000 K
CRI	≥ 80

### FLUORESCENT SOLUTION

TL09	5105009300-002
Light source	Compact fluorescent lamp (not included)
Lamp base	2G7
Weight	1.6 kg
Wattage	1x 9 W

### SPARE PARTS

### PART NO.

Opal cover	7925000800
Satin cover	7925000900
Lamp holder 2G7	7111022100

### ★ EXTRAS

- > Stainless steel housing
- > Emergency battery back-up
- > Different cable glands
- > 120 V AC execution

